

SP4T 系列四柱滑台型伺服压装机 SP4T 4-column slide type servo press

规格型号 Specification

SP4T - 010 - 200

压力 10KN	100KN	行程 100mm
pressure 20KN	150KN	stroke 200mm
30KN		300mm
50KN		

*其他规格可定制


Other specifications can be customized

应用范围 Scope of application

汽摩配件,电子电器,电机装配,铆钉铆接,轴承装配,仪器仪表,电动工具,阀门等行业的精密压装


Auto parts, electronic appliances, motor assembly, rivet riveting, bearing assembly, instrumentation, power tools. Valves and other industries precision press-fit

设备配置 Configuration




伺服电缸

SO2




三梁四柱带伺服滑台

FO1




多功能铝合金底座

BO1




PLC及功能模块

KO1




轮辐式测力传感器

PS1




位移传感器

WY1




电子手轮

DZ1




电脑显示器悬臂

BK1




电脑

HO4




XY力与位移曲线仪表

GM2




塑料按钮盒

ST2




安全光幕

GM1



三色报警灯

SD1



锁板

MT1

特点 Features

- | | |
|-----------------------|--|
| 1.位移和力两种控制模式 | 1. Displacement and force two control modes |
| 2.力与位移曲线 | 2. Force and displacement curve |
| 3.空行程快速行进, 慢速压装 | 3. Free travel fast, slow press fit |
| 4.位移传感器4μm/脉冲高精度 | 4 displacement sensor 4μm / pulse high precision |
| 5.进口压力传感器精度0.05%FS | 5.Imported pressure sensor accuracy of 0.05% FS |
| 6.力上下限, 位移上下限, 判断工件配合 | 6. Force upper and lower limits, displacement upper and lower limits, to determine the workpiece fit |
| 7.网线数据接口, 支持联网数据采集 | 7. Network cable data interface, support for network data acquisition |
| 8.历史数据保存, 压装参数可追溯 | 8. Historical data storage, press-fitting parameters can be traced |
| 9.闭环控制 | 9. Closed-loop control |
| 10.电子手轮轻松校对模具 | 10. Electronic hand wheel proofing easy to mold |

